



Description

Kemiko Easy Shine is a single component, waterborne, acrylic polymer wax for protecting and maintaining sealed concrete and many other finished substrates. Easy Shine is designed to be a maintenance coating with properties that include the ability to repel water, reduce scuffing and minimize marring. Easy Shine allows the substrate to breath, is low odor, low VOC, extremely user-friendly and comes in a high gloss or satin finish.

Applications

Kemiko Easy Shine can be applied to properly prepared Kemiko Stone Tone or Kemiko Rembrandt stained floors sealed with Kemiko Stone Tone Sealer II, Kemiko 100% Solids, Kemiko Water Base Epoxies, Kemiko Water Base Polyurethanes and Kemiko Aliphatic Polyaspartic coatings. Easy Shine is also compatible with many other sealed concrete products. Typical applications include: commercial kitchens, grocery stores, restaurants, showroom floors, walkways and many other interior surfaces requiring additional protection. Easy Shine is not intended to be applied over Kemiko Buff-On Wax II or Kemiko Repels Sealer. Kemiko Easy Shine is intended for interior use only.

Physical Characteristics

Kit Size	1 gallon and 5 gallon kits available
Colors Available	Clear, High Gloss and Satin finishes available
Volume Solids	<20% Volume Solids
VOC Contents	<250g/L (Theoretical)
Specific Gravity	1.03 (Theoretical)
Film Thickness	2-4 mils wet
Coverage per Kit	1 gallon: 400ft ² -800ft ² (37.2m ² -74.3m ²) at recommended film thickness 5 gallon: 2000ft ² -4000ft ² (186.0m ² -371.5m ²) at recommended film thickness <i>Note: Coverage rates will vary depending on surface texture and porosity.</i>
Dry/Recoat Time	Dry to Touch: 2-3 hours Light Foot Traffic: 8-10 hours Heavy Traffic: 20-24 hours Full Chemical and Physical Resistance Cure: 3-5 days Recoat Window: Within 10 hours after product reaches Dry to Touch state <i>Note: Product tested at 70°F, 30%RH. Dry and recoat times will depend on temperature, humidity and other conditions relative to the environment.</i>
Odor	Low
Primers	None required
Thinning	Do not thin
Clean Up	Clean tools with warm water, mild soap
Shelf Life	12 months from date of manufacture



Concrete Coatings & Floor Systems

TECHNICAL BULLETIN

Kemiko® Easy Shine Mop On Wax (48 Series)

Packaging Description

Weight per Kit:

1Gal: 8.57lbs (3.89kg) 5Gal: 42.85lbs (19.44kg)

Kemiko Easy Shine contains:

1Gal (3.78L) of product in a premeasured 1 gallon (3.78L) container
5Gal (18.82L) of product in a premeasured 5 gallon (18.82L) container

Environmental Conditions

Apply between 50°F-80°F (10°C-27°C) and 5°F above dew point. Avoid using in direct sunlight. Do not apply on rainy or foggy days.

Storage Conditions

Store between 50°F-100°F (10°C-32°C). Keep in a cool, well-ventilated area, away from direct sunlight and heat. Store in a segregated and safe area, avoiding all possible sources of ignition.

Safety

Care should be taken when using this product. During application, use proper protective equipment including, but not limited to: protective eyewear, proper respirator and protective gloves. Ensure work spaces are well-ventilated. Refer to the Application Bulletin for application information. Refer to product label and SDS carefully for more detailed safety information prior to use or handling.

Disclaimer

Information provided in this Technical Bulletin is based on laboratory testing and is used as a guideline only. Customer should test the material for their specific application and under their application conditions before using the product on a project.

Warranty

The following warranty is made in lieu of all other warranties, either expressed or implied. This product is manufactured of selected raw materials by skilled technicians. Neither seller nor manufacturer has any knowledge or control concerning the purchaser's use of this product and no warranty is made as to the results of any use. The only obligation of either seller or manufacturer shall be to replace any quantity of this product, which is proved to be defective. Any claim of defective product must be received in writing within one (1) year from date of shipment. Neither seller nor manufacturer assumes any liability for injury, loss or damage resulting from use of this product.

Contact EPMAR for any additional application information



Epmar Corporation

13240 Barton Circle, Whittier, CA 90605-3254
Ph: 562.946.8781 / Fax: 562.944.9958
www.epmar.com / www.kemiko.com