



Product Technical Data Sheet

MIRACOTE[®] MIRASTAMP LIQUID RELEASE (MLR)

1. PRODUCT DESCRIPTION

A. COMPOSITION

Miracote Mirastamp Liquid Release (MLR) is the best product available to facilitate imprinting operations in concrete, thin stamp overlay systems and micro overlay systems. Miracote MLR provides a dual function, working as both lubricating and parting agents, to protect impression-texturing tools and the value invested in decorative substrate materials. ML prevents tools from sticking to polymer cementitious overlay surfaces and concrete. MLR will prolong the life of the impression tool after the tool is worked into the substrate. MLR is specially formulated to work with many high-grade chemical resistant pump sprayers.

B. TYPICAL USES

MLR is specially formulated to work with Miracote Mirastamp, Miracote Micro-Topping and Colored Concrete imprinting systems. Advanced application technique of adding dry pigment to Liquid Release is easily facilitated.

2. INSTALLATION

A. Packaging

Miracote MLR is available in five liquid gallon pails and is used neat.

B. Application

Use pump type sprayer to liberally apply a light film onto the surface to be stamped. Avoid application onto areas not to be stamped.

Caution: Exercise extra caution to avoid over-spray onto clean Substrates that will later be coated with overlay materials. This is especially important when working with multi-colored overlay design and patterns.

In a convenient staging area over a protected surface, apply a mist of Miracote MLR to the impression tool. When applying on to the substrate, avoid application over an area of more than ten or fifteen square feet at a time as MLR can evaporate before the texturing tools are positioned and placed. Should this occur, apply additional MLR.

NOTE: Inert Dry Pigment can be added to MLR for delivery onto surfaces during the impression process to create accent veins, shading and color variegation.

Caution: Do not mix or work LMR – into the substrate material matrix. Corrections in process can be accomplished by placing texturing tools onto any surface that remains tender. Facilitate any correction by pressing out an unwanted impression or divot.

Working Caution: Obtain and read the MSDS sheets. MLR is a chemically erosive agent and can be slippery. Exercise caution when working with MLR. Generally, removal of MLR is not necessary. This MLR will naturally dissipate and will not affect integral Miracote Liquid Pigment coloration or Miracote Sealers. However, prudence does dictate reviewing the application instructions of any other stain, sealer or post release application material for specific requirements. When the impression – texturing application is completed, remove MLR from the tools by cleaning the tool's surface using soap and plain water.

Caution:

Miracote MLR is formulated to be compatible with most modern texturing tools manufactured out of polyurethane polymeric materials. There exist, however, tools that are not designed to work with Liquid Release. These are usually older tools or tools that are fabricated out of products of poor chemical resistance. Miracote recommends checking with both the manufacturer and the impression toolmaker to assure the investment in tools is protected and not compromised in any way.

3. PRODUCT AVAILABILITY

Crossfield Products Corp. maintains offices and/or factories at all addresses listed below. Factory Trained Contractors are established in all major trading areas in the United States, Canada and various European, Latin American and Far East nations.

4. CLEANING

Cleaning and disinfecting compounds and cleaning techniques can affect the color, gloss, texture and performance of the system. As a precautionary step, Crossfield recommends that the end-user test their cleaning and disinfecting compounds on a sample or on a small, out of the way finished area, utilizing the intended cleaning technique prior to cleaning the entire surface area. If no deleterious effects are observed, the procedure can be continued. If the cleaning and disinfecting compounds or cleaning techniques damage the system, modification of the cleaning material or techniques will be required. Contact your Representative for additional information.

5. MAINTENANCE

For maximum sheen and cleanability, floor should be routinely treated with conventional maintenance finish followed by ordinary buffing.

6. SPECIFICATION ASSISTANCE

Consult Crossfield Products Corp. for specification assistance, detailing, etc. This consultation is highly recommended prior to specification.

7. TESTING

The technical data contained herein is the result of tests made in Crossfield's laboratories or in independent laboratories using small scale equipment, following generally accepted trade practices. Although this information is believed to be true and accurate, the use of different equipment for testing under dissimilar conditions or the testing of samples produced under dissimilar conditions may develop substantially different results.

LIMITED WARRANTY

NO WARRANTY SHALL BE EFFECTIVE UNTIL THE TERMS AND CONDITIONS OF SALE SET FORTH IN CROSSFIELD PRODUCTS CORP. INVOICES ARE MET.

Crossfield Products Corp. warrants to the purchaser of its products that such products are free from manufacturing defect. Crossfield does not warrant or guarantee the workmanship performed by any person or firm installing its products. Crossfield's obligation under this warranty is limited solely to the original purchaser and solely to the remedy of replacement in kind of any product which Crossfield sold which may prove defective in manufacture within one year from date of installation, provided said product was stored correctly and installed within the product's shelf life, by the original purchaser and which Crossfield's examination shall disclose to Crossfield's satisfaction to be thus defective.

IN NO EVENT SHALL CROSSFIELD PRODUCTS CORP. BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. THIS WARRANTY IS EXPRESSLY GIVEN IN LIEU OF ALL OTHER WARRANTIES EXPRESSED OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR USE AND ALL OTHER OBLIGATIONS OR LIABILITIES ON CROSSFIELD'S PART, AND WE NEITHER ASSUME NOR AUTHORIZE ANY PERSON OR PERSONS TO ASSUME FOR US ANY OTHER LIABILITY IN CONNECTION WITH SALE OF A CROSSFIELD PRODUCT. THIS WARRANTY SHALL NOT APPLY TO ANY OF CROSSFIELD'S PRODUCTS, WHICH HAVE BEEN SUBJECT TO ADULTERATION, ALTERATION ABUSE OR MISUSE. CROSSFIELD PRODUCTS CORP. MAKES NO WARRANTY WHATSOEVER IN RESPECT TO ACCESSORIES, PARTS OR MATERIAL NOT SUPPLIED BY CROSSFIELD PRODUCTS CORP., WHICH ARE USED IN CONNECTION WITH ITS PRODUCTS. THE TERM "ORIGINAL PURCHASER" IN THIS WARRANTY MEANS THAT PERSON, CORPORATION OR ENTITY TO WHOM CROSSFIELD PRODUCTS CORP. SOLD ITS PRODUCTS. ANY ACTION TO ENFORCE ANY WARRANTY OR FOR BREACH OF CONTRACT OR ARISING OUT OF ANY CLAIM AGAINST CROSSFIELD PRODUCTS CORP. SHALL BE COMMENCED AND MAINTAINED ONLY IN A COURT OF COMPETENT JURISDICTION IN THE CONTINENTAL UNITED STATES OF AMERICA. THE PURCHASER ACCEPTS THESE TERMS AND CONDITIONS, AND HEREBY EXPRESSLY WAIVES ANY CLAIM TO ADDITIONAL DAMAGES.

CAUTION: ALWAYS KEEP OUT OF THE REACH OF CHILDREN.



MIRACOTE PRODUCT LINE Crossfield Products Corp.

West Coast Office
3000 E. Harcourt Street
Rancho Dominguez, CA
90221
310-886-9100
310-886-9119 fax

East Coast Office
140 Valley Road
Roselle Park, NJ
07204
908-245-2800
908-245-0659 fax

www.miracote.com