



Epoxy &  
Polyurethane  
Manufacturing and  
Research

## TECHNICAL BULLETIN

### KEMIKO® EASY SHINE Acrylic Polymer Wax (Mop On)

#### Description

KEMIKO® EASY SHINE is a low-VOC, extremely user-friendly, waterborne acrylic polymer wax for protecting and maintaining sealed concrete and many other finished substrates. KEMIKO EASY SHINE is a single component product that is designed to repel water, reduce scuffing and marring, allows substrate to breath, is low odor, and produces a deep rich shine.

#### Applications

KEMIKO® EASY SHINE is applied to properly prepared Kemiko® or Rembrandt stained floors sealed with Kemiko® Stone-Tone Sealer II, Sta-Crete® 100% Solids and Water Base Epoxies, Sta-Crete® 2700 WB Polyurethane, Sta-Crete® 3300 Aliphatic Polyurea and is compatible with many other sealed concrete products. Typical applications include commercial kitchens, grocery stores, restaurants, showroom floors, walkways, and many other interior surfaces requiring additional protection. Excellent replacement product for high VOC solvent base water repellents and sealers with excellent wetting properties.

#### Performance

VOC	Low
Leveling & Flow	Excellent. Use Brush, Roll, Mop-On or Spray Applications

#### Physical Characteristics

Volume Solids	26.3%
Packaging	1 <sup>s</sup> , 5 <sup>s</sup>
Flash Point	None
Gloss	High Gloss Finish
Dry Time	@70°F. 50% RH 1 Hour Light Foot Traffic 24-48 Hours To Service
Appearance	Milky-White Liquid
Coverage	1500-2000 ft <sup>2</sup> per gallon, per coat
Thinning	None Required. Use mild soap and tap water for clean up.

#### Surface Preparation

##### Finished Floor –

All visible oil, grease, sludge, stain residue and any other contaminants shall be removed prior to any KEMIKO® EASY SHINE application. Surface shall be cured, dry and free from any deleterious matter or grime. Use KEMIKO® EASY STRIP to remove heavy wax build up, grease, oils and grime.

#### Application Methods

##### Brush –

Use top-quality nylon bristle brush for best film properties.

##### Roller –

Lambswool or similar cover with phenolic core, ¼ - ½ inch nap thickness. Soft lambswool pads and sponge pads may also be used to evenly spread material.



Epoxy &  
Polyurethane  
Manufacturing and  
Research

## TECHNICAL BULLETIN

### KEMIKO® EASY SHINE Acrylic Polymer Wax (Mop On)

#### **Spray –**

Low pressure “Hudson” type sprayers or conventional air assisted sprayers set at very low pressure (<10 psi). Backrolling may be necessary to produce even finished film.

#### **Environment –**

Apply between 50°F. – 100°F. and 5°F. above dewpoint. Do not store in direct sunlight. Protect from freezing. Do not apply to wet or frosted surfaces.

#### **Safety –**

**May be irritating to eyes and skin!** Wear gloves and eye protection during application. Areas such as decks, sloped concrete, or other surfaces subjected to water may become slippery if coated with KEMIKO® EASY SHINE. If you must seal these surfaces, keep the sealer film build-up to a minimum.

**Contact EPMAR for any additional application information.**

#### **Warranty**

The following warranty is made in lieu of all other warranties, either expressed or implied. This product is manufactured of selected raw materials by skilled technicians. Neither seller nor manufacturer has any knowledge or control concerning the purchaser's use of this product and no warranty is made as to the results of any use. The only obligation of either seller or manufacturer shall be to replace any quantity of this product, which is proved to be defective. Any claim of defective product must be received in writing within one (1) year from date of shipment. Neither seller nor manufacturer assumes any liability for injury, loss, or damage resulting from use of this product.

**Service is part of our formula**

#### **Epmar Corporation**

13210 Barton Circle, Santa Fe Springs, CA 90605-3254

Ph: 562.946.8781 / Fax: 562.944.9958

E-Mail: [epmar@quakerchem.com](mailto:epmar@quakerchem.com) Web Site: [www.epmar.com](http://www.epmar.com)