

DECO LIQUID RELEASE

Bubble Gum Scented Decorative Clear Liquid Release Agent

Product Description

Deco Liquid Release is a bubble gum scented colorless liquid release agent specially formulated as a bond breaker between freshly poured concrete and decorative tools such as stamp mats, texture skins, stencils, etc. It creates a lubricating barrier that extends the life of the texturing tools by decreasing the friction between the concrete and the tools. Deco Liquid Release evaporates leaving non residue behind, meaning less clean up and labor cost. This characteristic makes it perfect for both exterior and interior applications.

Benefits & Features

- Special formula creates an unmatched barrier between tools and the fresh concrete surface.
- It's bubble gum scent makes this release agent pleasant to work with.
- Evaporation and no clean up make this product economical and easy to use.

Recommended Applications

Deco Liquid Release is recommended for use as a bond breaker between freshly placed interior or exterior concrete surfaces and decorative texturing and stenciling tools.

Technical Information

Solids	0%	Wet Appearance	Clear
Drying Time	1-2 Hours	Dry Appearance	Product Evaporates N/A
Re-Coat Time	N/A	VOC Content	N/A
Foot Traffic	N/A	Blush Resistance	N/A
Wheel Traffic	N/A	Solvent Resistance	N/A
Application Temp	40°F - 85°F	Concrete Adhesion	N/A

***Please note that low air and/or concrete temperatures and/or relative humidity may extend drying times. Follow recommended coverage rates for best results.

Specifications/Compliances

N/A

Approximate Coverage Rates

Deco Liquid Release covers approximately 150-200 square feet per gallon on freshly placed concrete.

*Coverage rates vary depending upon surface porosity and texture, and application method. Excessive build up should be avoided.

Shelf Life

Deco Liquid Release has a shelf life of up to two years in it's original, sealed, unopened container.

Packaging

Deco Liquid Release is packaged in 1 gallon cans, 5 gallon pails and 55 gallon drums.

ORRVILLE

133 North Kohler Road
Orrville, Ohio 44667
(330) 682-5678

CLEVELAND

7941 Granger Road
Cleveland, Ohio 44125
(216) 573-0770

COLUMBUS

690 Harrison Drive
Columbus, Ohio 43204
(614) 253-3326



www.eco-cretesupply.com

Instructions for Use

Surface Preparation: Trowel and finish freshly placed concrete surfaces to prepare for stamping or stenciling process. At the time that the concrete has reached it's "plastic" like state when texturing is mainly desired, Deco Liquid Release should be applied between the texturing tools and the freshly placed concrete surface.

Substrate temperature must be no less than 40 degrees F and not exceed 80 degrees F.

Application: Apply liberally using a solvent resistant pump up sprayer in a mist fashion to the texturing tools to be used and the concrete surface, but only on the area where the next few texture mats or stencil will go. It is recommended to apply only over an area of about 10-20 sq. ft. at a time to avoid evaporation of the release agent. This is especially important on cool, windy days. Continue this process until the texturing application is complete. Wash the release agent off the texturing tools simply by spraying them with water.

*Never trowel the release agent into the freshly placed concrete surface as the correct method of fixing a blemish is to use a matching texturing skin to imprint and fix that area.

**Sealing decorative concrete is imperative to a long lasting concrete surface. It is recommended to wait 28 days prior to sealing concrete to allow the entire area enough time to cure.

Please Note: It is always recommended to test the product in a small, inconspicuous area (on the same concrete substrate) for desired results prior to application.

Clean-Up

Use soap and water. Dispose of containers in accordance with local and federal regulations.

Product Removal

Not applicable.

Precautions & Limitations

- Deco Liquid Release will not freeze during storage, however, allow temperature to rise to 50°F prior to application.
- All HVAC ventilation ducts should be somehow blocked prior to application so solvents fumes are not distributed.
- Keep away from open flames. Deco Liquid Release is flammable and is very susceptible to ignition.
- It is not recommended to apply Deco Liquid Release over cured concrete as impressions can not be made.
- Coverage rates depend upon many conditions including application method, surface porosity, applicator, etc.
- Deco Liquid Release was designed for exterior as well as interior decorative concrete.
- Deco Liquid Release is not resistant to brake fluid, gasoline, and many similar products.
- It is not recommended to thin Deco Liquid Release.
- It is recommended to test this product prior to using on entire application.

Special Notes

Please consult Safety Data Sheet (SDS) and read warranty information prior to use. This information can be requested by contacting customer service at 330-682-5678.

ORRVILLE

133 North Kohler Road
Orrville, Ohio 44667
(330) 682-5678

CLEVELAND

7941 Granger Road
Cleveland, Ohio 44125
(216) 573-0770

COLUMBUS

690 Harrison Drive
Columbus, Ohio 43204
(614) 253-3326



www.deco-cretesupply.com