



Concrete
Coatings &
Floor Systems

TECHNICAL BULLETIN

Kemiko® Easy Shine Acrylic Polymer Wax (Mop On)

Description

Kemiko Easy Shine is a low-VOC, extremely user-friendly, waterborne acrylic polymer wax for protecting and maintaining sealed concrete and many other finished substrates. Kemiko Easy Shine is a single component product that is designed to repel water, reduce scuffing and marring. Kemiko Easy Shine allows substrate to breathe, is low odor, and produces a deep rich shine.

Applications

Kemiko Easy Shine is applied to properly prepared Kemiko or Rembrandt stained floors sealed with Kemiko Stone Tone Sealer II, Kemiko 100% Solids and Water Base Epoxies, Kemiko SS2700 Water Base Polyurethane, Kemiko SS3300 Aliphatic Polyaspartic and is compatible with many other sealed concrete products. Typical applications include commercial kitchens, grocery stores, restaurants, showroom floors, walkways, and many other interior surfaces requiring additional protection. Excellent replacement product for high VOC solvent base water repellents and sealers with excellent wetting properties. **It is not to be applied over Kemiko Buff-On Wax II.**

Performance

VOC	Low
Leveling & Flow	Excellent. Spray application & follow-up with pad or mop

Physical Characteristics

Volume Solids	26.3%
Packaging	1 gal & 5 gal (premeasured kits)
Flash Point	None
Gloss	High Gloss/Satin
Dry Time	@ 70°F 50% RH 1 hour light foot traffic 24-48 hours to service
Appearance	Milky-white liquid
Coverage	1500-2000 ft ² per gallon, per coat
Thinning	None required

Surface Preparation

Finished Floor —

All visible oil, grease, sludge, stain residue and any other contaminants shall be removed prior to any Kemiko Easy Shine application. Surface shall be cured, dry and free from any deleterious matter or grime. Use Kemiko Easy Strip to remove heavy wax buildup, grease, oils and grime.

Clean Up — Use mild soap and tap water for cleanup.



**Concrete
Coatings &
Floor Systems**

TECHNICAL BULLETIN

Kemiko® Easy Shine Acrylic Polymer Wax (Mop On)

Application Methods

Spray —

Use a professional type low pressure “Hudson” type sprayer and immediately follow along behind with a micro fiber pad or mop to create an even finished film massaging it onto the floor surface in somewhat of a figure eight, back and forth motion. Drying time is 20-30 minutes.

Environment —

Apply between 50°F – 100°F and 5°F above dew point. Do not store in direct sunlight. Protect from freezing. Do not apply to wet or frosted surfaces.

Safety —

May be irritating to eyes and skin! Wear gloves and eye protection during application. Areas such as decks, sloped concrete, or other surfaces subjected to water may become slippery if coated with Kemiko Easy Shine. If you must seal these surfaces, keep the sealer film buildup to a minimum.

Contact EPMAR for any additional application information.

Warranty

The following warranty is made in lieu of all other warranties, either expressed or implied. This product is manufactured of selected raw materials by skilled technicians. Neither seller nor manufacturer has any knowledge or control concerning the purchaser's use of this product and no warranty is made as to the results of any use. The only obligation of either seller or manufacturer shall be to replace any quantity of this product, which is proved to be defective. Any claim of defective product must be received in writing within one (1) year from date of shipment. Neither seller nor manufacturer assumes any liability for injury, loss, or damage resulting from use of this product.



Epmar Corporation
13240 Barton Circle, Santa Fe Springs, CA 90605-3254
Ph: 562.946.8781 / Fax: 562.944.9958
www.epmar.com / www.kemiko.com

Rev. 110514