SAFE-THAW

Liquid Sprayable Concrete & Paver De-icer

Product Description

An all natural and environmentally safe de-icer. It is water soluble and will not stain surfaces. Can reduce snow/ice accumulation if applied no more than 1.5 - 2 hours before a storm. Use caution when applying Safe-Thaw in temperatures over 36°F because it can cause a slippery surface. Safe-Thaw is a non-toxic solution and considered a safe product for pets and children. Most effective between temperatures 15°F - 32°F.

Benefits & Features

- Helps melt snow and ice at lower temperatures than salt
- Superior penetration of residual ice and snow packs
- Can stop 1-2" of snow or ice before it accumulates on the pavement
- 10-14 day residual reactivation effect
- Colorless and odorless
- Low viscosity
- One gallon provides the same ground coverage as 50 lbs. of salt or pellets
- Pet safe formula
- Biodegradable and environmentally safe
- Water soluble
- Non-staining

Technical Information

 $\begin{array}{lll} \text{pH (1:4 Solution)} & 4.9 \\ \text{Corrosion Rate} & 8.4\% \\ \text{MgCL}_2 & 25\% \\ \text{Phosphorus} & 14.2 \text{ppm} \\ \text{Freeze Point} & -61^{\circ}\text{C/-77}^{\circ}\text{F} \end{array}$

Specifications/Compliances

N/A

Approximate Coverage Rates

One gallon covers approximately 200 - 250 square feet

Where to Use

- Sidewalks/Walkways
- Driveways
- Patios
- Parking Lots
- Steps
- Porches

Packaging

5 gallon drum

ORRVILLE 133 North Kohler Road Orrville, Ohio 44667 (330) 682-5678

CLEVELAND
7941 Granger Road
Cleveland, Ohio 44125
(216) 317-2455

COLUMBUS 723 Taylor Avenue Columbus, Ohio 43219 (614) 253-3326





Instructions for Use

Use a plastic or stainless steel sprayer that can produce a mist or stream. Apply at full strength on driveways, walkways, steps, porches, roof and eaves. For de-icing, apply in a stream to packed snow and ice. Then allow 60 - 90 minutes for maximum melting before shoveling. For thick ice, you can use with sand to speed the process up.

Curing

N/A

Special Notes

Please consult Material Safety Data Sheet (MSDS) and read warranty information prior to use. This information can be requested by contacting customer service at 330-682-5678.

ORRVILLE 133 North Kohler Road Orrville, Ohio 44667 (330) 682-5678

CLEVELAND 7941 Granger Road Cleveland, Ohio 44125 (216) 317-2455 COLUMBUS 723 Taylor Avenue Columbus, Ohio 43219 (614) 253-3326



