

EASY PATCH

Concrete Repair and Resurfacing Mortar

Product Description

Easy Patch is a one component, polymer modified, high performance repair and resurfacing mortar. Easy Patch is simply mixed with water and applied to concrete, wood, plywood or ceramic, from featheredge to 1.5" thick in one application. Apply horizontal, vertical or overhead. Apply with trowel, brush or broom. Product sets in 20 to 45 minutes and is ready for light traffic in 3 to 4 hours at 70°F. Easy Patch is a special blend of cement, aggregate and exclusive modifiers. Designed for general purpose and high performance concrete repair or resurfacing applications.

Benefits & Features

- Polymer modified
- Portland cement based
- Self-curing, self-bonding
- Waterproof underlayment
- Short setting time - under an hour
- One component - just add water

Technical Information

Compressive Strength, 28 day	Exceeds 4500 psi	ASTM C42
Compressive Strength, 7 day	Exceeds 3000 psi	ASTM C42
Compressive Strength, 1 day	Exceeds 2500 psi	ASTM C42
Freeze/Thaw Durability	Excellent	ASTM C666
Bond Strength	Exceeds 150 psi	ACI 503 R
Color	Concrete gray	
Set Time	20 minutes	

Specifications/Compliances

N/A

Approximate Coverage Rates

One bag covers approximately 50 square feet at 1/8" thick

Where to Use

- Smoothing and filling depressions
- On concrete, wood, plywood, ceramic
- Naval vessels
- Underlayment for tile & carpet
- Over prepared waterproof adhesives
- Driveways, sidewalks
- Interior or exterior

Packaging

50 lb Bag

ORRVILLE

133 North Kohler Road
Orrville, Ohio 44667
(330) 682-5678

CLEVELAND

7941 Granger Road
Cleveland, Ohio 44125
(216) 573-0770

COLUMBUS

690 Harrison Drive
Columbus, Ohio 43204
(614) 253-3326



www.eco-cretesupply.com

Instructions for Use

Surface Preparation: Surface preparation is critical to achieve long lasting results. Existing concrete surface shall be clean, sound, and free of oil, grease, laitance, curing compounds, or any other foreign substance. Preparing surface by mechanical means, such as grinding or shot blasting, is recommended. Areas treated with product must be free of dust and any foreign matter prior to topping application. The use of Sure Bond 100 as a primer is highly recommended on all surfaces.

Mixing: Approximately 1 gallon (4 quarts) of water is required to mix 40 lb of product for troweling. Rub or scratch mixed material onto surface just prior to application. For brush or broom applications, 1.5 gallons of water is required. Force action mixing for 2 to 3 minutes is recommended.

Application: Rub or scratch part of the mixed material onto surface just prior to application. Trowel, brush or broom apply to clean surface. For uniform finish, apply with brush or broom in same direction.

For Best Results: Apply to clean, dry sound substrate above 40°F. Rub or scratch part of the mixed material onto surface just prior to application. Do not allow rub or scratch coat to dry before application. Check moisture content (mat test) prior to applying any waterproof topping. Do not retemper already mixed material.

Curing

Avoid applications in high winds, excessive heat or blowing air directly on freshly placed product. Product sets in 20 to 45 minutes. Allow 3 to 4 hours for light traffic on horizontal repairs.

Special Notes

Please consult Material Safety Data Sheet (MSDS) and read warranty information prior to use. This information can be requested by contacting customer service at 330-682-5678.

ORRVILLE

133 North Kohler Road
Orrville, Ohio 44667
(330) 682-5678

CLEVELAND

7941 Granger Road
Cleveland, Ohio 44125
(216) 573-0770

COLUMBUS

690 Harrison Drive
Columbus, Ohio 43204
(614) 253-3326



www.deco-cretesupply.com