FAST 5 TO 20

Iron Oxide Pigment

Product Description

Fast 5 to 20 by Deco-Crete Supply is an economical system that allows you to stock 5 base colors to create 20 custom colors using our simple formula. Each color is packaged in lightweight 10 lb water-soluble bags making this color system easy to use. Fast 5 to 20 pigment can be used to color smooth trowel, broom finish, countertops, walls, plus many more applications. By using Deco-Crete Texturing Tools, Color Hardeners and Antique Releases you can create more colors and design options for any decorative concrete project.

Benefits & Features

- Easy dissolving water soluble bag
- Stock only 5 colors to make 20 colors
- Most popular shades from all manufacturers
- Easy to handle 10lb bags
- UV-resistant color

Technical Information

VOC (Volatile Organic Compound) Content Appearance Composition and Materials O grams/liter
Dry Powder
Pigments are Red, Yellow, & Black Iron Oxides

Applications

- Smooth trowel
- Broom finish
- Countertops
- Walls
- Stamped Concrete

Packaging

Lightweight 10 lb water-soluble bags with protective outer bag.

ORRVILLE 133 North Kohler Road Orrville, Ohio 44667 (330) 682-5678

CLEVELAND 7941 Granger Road Cleveland, Ohio 44125 (216) 573-0770 COLUMBUS 723 Taylor Avenue Columbus, Ohio 43219 (614) 253-3326





Instructions for Use

Preparation of Jobsite: Concrete will not cure evenly and inconsistent coloring may occur if poured over an inconsistent sub-grade, plastic, mix of dirt, wood, asphalt, or existing concrete. If the majority of the water in the concrete is forced to the surface to evaporate, efflorescence may occur. In hot conditions, sub-grade must be kept moist before each pour. This keeps the water in the concrete from being absorbed too quickly into the stone base. Make sure there is good drainage and the aggregate is compacted. Problems can occur if pouring concrete over plastic, such as: excessive bleed water, shrinkage, uneven drying time, and efflorescence. If pouring over plastic is required on job sites, consider using 2"- 4" of sand or gravel between the plastic and concrete. Alteration to the mix design may need to be made if pouring directly onto plastic.

Mixing: Use the same mix design, water content and mixing time every load to ensure consistent color from batch to batch. Every job should be a minimum cement content of 6 sacks per cubic yard and a maximum 4" slump. The color can be added to the concrete at any time, but is recommended that it be added at the concrete plant. Concrete load must be kept to 8 yards per truck to ensure proper color dispersion. With the load of concrete turned to the back of the mixer, place the water soluble bag directly onto the concrete. Mix for a minimum of 15 minutes. Once pour has begun, additional water should be kept at a minimum. If the slump and mix design are not consistent from batch to batch, color variation may occur. A JOBSITE SAMPLE IS RECOMMENDED.

Additives: DO NOT USE CALCIUM CHLORIDE. Plasticizers, water reducers, non-cholride accelerators, and air entraining products that are designed for colored concrete may be used.

Curing: DO NOT COVER, FOG OR WET CURE COLORED SURFACES.

Warranty: PROFESSIONAL USE ONLY. Product is intended for licensed concrete contractors, that have the experience and training to use this product. End user is responsible for product aptness and assumes all risks and liability. Obligations of the manufacturer will be limited to refunding the purchase price of replacing the product if deemed defective.

Clean-up

Use soap and water. Dispose of containers in accordance with local, state and federal regulations.

Shelf Life

Indefinite when in its original, unopened container, stored at room temperature.

Special Notes

Please consult Safety Data Sheet (SDS) and read warranty information prior to use. This information can be requested by contacting customer service at 330-682-5678.

ORRVILLE 133 North Kohler Road Orrville, Ohio 44667 (330) 682-5678 CLEVELAND
7941 Granger Road
Cleveland, Ohio 44125
(216) 573-0770

COLUMBUS 723 Taylor Avenue Columbus, Ohio 43219 (614) 253-3326



