



REVIVAL

Opaque Color Coating

PRODUCT DESCRIPTION

Deco-Crete Revival is an opaque color coating that can be used to give a whole new look to any unsealed existing concrete surfaces. It will completely cover discolorations, stains, or any other blemishes that may be present. Revival may be used on interior or exterior, stamped, broomed, or swirl finished concrete along with other cementitious surfaces. It is formulated to match Deco-Crete's most popular *Color Hardener* & *Integral Color* Systems as well as a natural color similar to cured concrete.

TECHNICAL INFO

- + Coverage Rate _____ 200 sq. ft. per kit*
- + Foot Traffic _____ 3 – 6 hrs.
- + Wheel Traffic _____ 48 hrs.
- + Packaging _____ 32oz. (A) & 6 oz. (B)
- + Shelf Life _____ 1 year
- + Clean-Up _____ Soap & Water

*Approximately 200 sq. ft. per kit which includes 2 coats

RECOMMENDED APPLICATIONS

- + Interior or Exterior Concrete
- + Stamped Concrete
- + Broom Finish Concrete
- + Swirl Finish Concrete



QUICK FACTS

- + 20 Standard Colors matching Deco-Crete's *Color Hardener* & *Integral Color* Systems
- + Great for Restoration Work
- + Fixes Color Issues on New or Old Concrete
- + Complete Opaque Coverage
- + MADE IN THE U.S.A.



REVIVAL

Opaque Color Coating

INSTRUCTIONS FOR USE

DO NOT APPLY IF RAIN IS FORECAST WITHIN 8 HRS. AFTER APPLICATION.

COVERAGE RATE

Approximately 200 sq. ft. per kit. (includes 2 coats)

SURFACE PREP

Concrete substrate must be a minimum of 30 days old & free of all sealers, membranes, & contaminants. Thoroughly power wash with a minimum of 3500 Psi & allow to dry for 24 hrs.

MIXING

Empty Part A (32 oz.) into a clean 5 gal. bucket. Fill Part A container with water & shake thoroughly, then dump into mixing pail. Repeat the fill, shake, & dump step two more times for a total of 3 times. Empty Part B (6 oz.) into bucket. Using a paint stick, scrape any remaining contents of Part B container into mixing pail. Fill Part B container with water & shake thoroughly, then dump into mixing pail. Mix with drill mixer on low speed for 1 min. Scrape sides & bottom of mixing pail with paint stick, continue mixing for an additional minute.

**It is normal for product to foam in mixing pail.*

APPLICATION

Revival is a two coat system. Concrete substrate needs to be a minimum of 50°F prior to application. Apply using a car wash brush. Dip brush into bucket, agitate mixture, then apply generously to surface in a circular motion. While first coat is drying, continue to rebrush with a soft bristle flag tip broom to distribute color evenly. In warmer weather a second person is highly recommended, otherwise utilize saw cuts to work in smaller areas. Continue brushing with a soft bristle flag tip broom until surface is completely dry. A second coat of Revival will be required. Apply second coat as soon as first coat is dry & tack-free. Remix product using drill mixer prior to second coat to ensure proper pigment dispersion, then apply second coat immediately in same fashion as first. Any left over product may be used for subsequent coats for approximately 8 hrs. as long as it is kept in a sealed container that's stored in a cooler place. Dry time may vary depending on weather conditons & porosity of surface. At 70°F product will dry in about 30 min. On hot days, it is recommended to apply product in the morning when the weather is cooler & the slab is out of direct sunlight. It is recommended to let Revival dry for 3-6 hrs. before applying *Deco-Crete Texture Enhancer*. Allow to dry 24 hrs. before applying concrete sealer.

ANTIQUING & SEALING

If applying Revival to stamped concrete the use of *Deco-Crete Texture Enhancer* is recommended to create an antiquing effect. Please refer to *Deco-Crete Texure Enhancer* Tech Sheet for full instructions. *Deco-Crete D-One Sealer* is recommended to protect from staining & to bring out full color of *Deco-Crete Texture Enhancer*.

PRO TIPS

- + For maximum bond to concrete substrate, use *Deco-Crete Deco-Prep* during cleaning process
- + Agitate material in mixing bucket with every dip of car wash brush during application

FOR PROFESSIONAL USE ONLY. This product is intended for use by licensed concrete contractors that have the experience & training to use this product. The colors shown on the color chart are an approximate representation of concrete with a flat trowel & unsealed finish. Deco-Crete is not responsible for application methods, finishing techniques, or any other variables that cannot guarantee the final appearance to be an exact match to the color chart. Deco-Crete strongly recommends that a representative jobsite sample be made for each product.

STORAGE

- + Store in a cool place, out of direct sunlight. Keep away from sources of excessive heat, ignition points, open flames, or any reactive material(s). Keep container(s) closed when in storage.



For tutorials & even more decorative concrete content,
follow the QR code here or find us on social media.



www.eco-cretesupply.com