



Easy Strip Form Releaser Specification Sheet

1. PRODUCT NAME

Easy Strip Form Releaser

2. MANUFACTURER

Deco-Crete Supply, Inc.
133 North Kohler Rd.
Orrville, OH 44667
330-682-5678

3. PRODUCT DESCRIPTION

Basic Use: Easy Strip Form Releaser permits removal of forms, formliners, pallets, etc. from hardened concrete. It:

- Helps minimize clean-up of forms
- Promotes easy form stripping
- Is non-staining when used properly
- Properly applied does not "kill" concrete surfaces
- Good on aluminum forms
- Does not cause efflorescence

Limitations: Not recommended for forms or formliners made from expanded polystyrene, SBR, or natural rubber or latexes made of these.

4. TECHNICAL DATA

Please see Tables.

5. APPLICATION

Preparatory Work: Form surfaces should be clean, dry, and free from contaminants. Apply Easy Strip just minutes before concrete is placed or up to 7 days before if treated surface is protected.

Apply with any type applicator or technique. Use a sprayer, roller, brush, or mop.

Too much release agent will cause bugholes concrete build-up, soft spots, staining, and an increased difficulty in stripping.

Storage: Factory sealed containers will keep up to 2 years at temperatures from -20°F to 140°F

TABLE OF PROPERTIES

Color	Straw
Opacity	Clear
Freeze Temperature	-20°F (-29°C)
Freeze Damage	None
Flash Point	320°F (160°C)
Viscosity (centipoises)	15 @ 68°F (20°C)
Solids	None
Pounds per gallon	7.3
VOC	250 g/L

Composition: A proprietary blend of vegetable oils in petroleum based oils. Contains no silicones...no carcinogens.

(-30°C to 60°C). Easy Strip is a class 3B liquid for purposes of meeting OSHA storage requirements (Section 1910.106).

Precautions: Keep out of reach of children. Avoid prolonged contact with the skin. Use with adequate ventilation. See Material Safety Data Sheet for additional information.

6. AVAILABILITY

Availability: Easy Strip is available in 1 and 5 gallon containers; orange and white striped 55 gallon drums and 275 gallon MegaPaks.

COVERAGE WITH EASY STRIP

Form Surface	(sq ft/gal)
Hard & Smooth	1,000
Pre-oiled Plywood	600
Untreated Plywood	500

7. LIMITED WARRANTY

Deco-Crete Supply, Inc. warrants the product against defects in materials for a period of 1 year from purchase. If Deco-Crete receives notice of such defects during the warranty period, Deco-Crete at its option will either replace the product or refund the purchase price. THE WARRANTY SET FORTH ABOVE IS EXCLUSIVE AND NO OTHER WARRANTY, WHETHER WRITTEN OR ORAL, IS EXPRESSED OR IMPLIED. DECO-CRETE SPECIFICALLY DISCLAIMS THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE REMEDIES PROVIDED HEREIN ARE BUYER'S SOLE AND EXCLUSIVE REMEDIES. IN NO EVENT SHALL DECO-CRETE SUPPLY, INC. BE LIABLE FOR DIRECT, INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES INCLUDING LOSS OF PROFIT) WHETHER BASED ON CONTRACT, TORT OR ANY OTHER LEGAL THEORY.

TABLE OF FORM AND FORMLINER COMPATIBILITY

Plywood	All Grades, Pre-oiled, Overlaid (LDO, MDO, HDO)
Plastics	Fiberglass Reinforced, ABS, PVC
Coatings	Epoxy, Urethane
Elastomerics	Urethane, Silicone
Steel	
Aluminum	

8. MAINTENANCE

Cover, or store drums on side to prevent water (i.e. moisture, condensation, rain) from entering the drum.