

REJUVENATOR

Solvent Based Restoration Blend

Product Description

Rejuvenator is made up of a strong blend of aromatic and ketone solvents and surfactants. It is used to restore heavily coated existing solvent based acrylic sealers that have started to soften, fade, peel, crack, delaminate, and deteriorate. Rejuvenator also clears up white spots or blushing due to moisture content issues. Rejuvenator melts the heavily coated existing solvent based acrylic sealer, and helps restore the original appearance without adding more acrylic to allow the sealer to wear off naturally over time without stripping the existing bulk of the coating.

Benefits & Features

- Superior ability to fix excessively coated acrylic sealer issues as opposed to expensive coating stripping.
- This product revitalizes the existing surface without adding more acrylic.
- Very fast drying time highly reduces the risk of trapped solvent or other types of moisture issues
- It's ultra low viscosity allows for easy spraying through an acetone resistant sprayer.

Recommended Applications

Rejuvenator is recommended for use on heavily coated existing sealed surfaces where softening, fading, peeling, cracking, delamination, and deterioration has taken place and a new sealed look is desired without the need of additional acrylic.

Technical Information

Solids	0%	Wet Appearance	Clear
Drying Time	30 min. - 1 Hour	Dry Appearance	Clear
Re-Coat Time	4-24 Hours	VOC Content	< 100 g/l
Foot Traffic	4-6 Hours	Blush Resistance	Superior
Wheel Traffic	24-48 Hours	Solvent Resistance	N/A
Application Temp	40°F - 85°F	Concrete Adhesion	N/A

***Please note that low air and/or concrete temperatures and/or relative humidity may extend drying times. Follow recommended coverage rates for best results.

Specifications/Compliances

Not Applicable.

Approximate Coverage Rates

Old (sealed) concrete 100-200 ft²

*Coverage rates vary depending upon surface porosity and texture, and application method. Excessive build up should be avoided.

Shelf Life

Rejuvenator has a shelf life of up to two years in it's original, sealed, unopened container.

Packaging

Rejuvenator is packaged in 1 gallon cans, 5 gallon pails and 55 gallon drums.

ORRVILLE

133 North Kohler Road
Orrville, Ohio 44667
(330) 682-5678

CLEVELAND

7941 Granger Road
Cleveland, Ohio 44125
(216) 573-0770

COLUMBUS

690 Harrison Drive
Columbus, Ohio 43204
(614) 253-3326



Instructions for Use

Surface Preparation: Concrete surface must be clean and free of all contaminants and water. Do not apply if rain is forecast within 24 hours. If moisture is present or if the surface is not clean and free of all contaminants, this product may not be able to fix the original issue.

Substrate temperature must be no less than 40 degrees F and not exceed 80 degrees F. If applied outside these limits this product may not achieve adequate film formation and may have excessive air entrapment, bubbles, blushing or hazing.

Mixing: Stir well before using. Material may separate during long term storage.

Application: Apply using a 3/8" - 1/2" nap roller cover heavily using slow, long even uniform strokes at approximately 100-200 square feet per gallon depending on porosity and texture of substrate to allow existing coating adequate time to re-emulsify. An acetone resistant sprayer may be used as well. Applying too thin may yield less than required results. Allow Rejuvenator to dry for 24 hours for light traffic and at least 48 hours for heavy traffic. If applying two coats, wait approximately 4-6 hours between coats.

Please Note: it is always recommended to test the product in a small, inconspicuous area (on the same concrete substrate) for desired results prior to application. Coverage rates may vary for all coatings and substrates depending on porosity, density, texture, etc. If applying by spray method, extended coverage rates may be achieved, but be aware that less material will be applied and inadequate film formation or performance expectations may be limited.

Clean-Up

Use Xylene. Dispose of containers in accordance with local and federal regulations.

Product Removal

Not Applicable

Precautions & Limitations

- Rejuvenator will not freeze during storage, however, allow temperature to rise to 50°F prior to application.
- All HVAC ventilation ducts should be somehow blocked prior to application so solvent fumes are not distributed.
- Keep away from open flames. Rejuvenator is flammable and is very susceptible to ignition.
- It is not recommended to apply Rejuvenator over carpet, tile and other types of floor adhesives.
- Coverage rates depend upon many conditions including application method, surface porosity, application, etc.
- Rejuvenator was designed to revitalize heavily coated old and deteriorated concrete sealer applications.
- Please be aware that this product when dried may be slippery when wet.
- Rejuvenator does not make existing coating resistant to brake fluid, gasoline, and many similar products.
- It is not recommended to thin Rejuvenator. Improper thinning may cause sealer to delaminate in a short time frame.
- Rejuvenator can be applied to most sealer applications but may be incompatible to some. Test prior to use.

Special Notes

Please consult Safety Data Sheet (SDS) and read warranty information prior to use. This information can be requested by contacting customer service at 330-682-5678.

ORRVILLE

133 North Kohler Road
Orrville, Ohio 44667
(330) 682-5678

CLEVELAND

7941 Granger Road
Cleveland, Ohio 44125
(216) 573-0770

COLUMBUS

690 Harrison Drive
Columbus, Ohio 43204
(614) 253-3326



www.deco-cretesupply.com